


SarviceManual



12 V 🗇







Published by Philips Car Systems Printed in The Netherlands © Copyright reserved Subject to modification

4822 725 23515





CONTENTS

Page	2	Technical datas
Page	3	Controls
Page	4	Display indications
Page	5	INIT Mode, Notes
Page	6	Connectorblock - pin allocations, key- and display test, romcode version
Page	7	Checks
Page	8	Low voltage control, adjustments
Page	9	Wiring diagram
Page	10	Front PWB's
Page	11	Front circuit
Page	12	Main PWB
Page	13	FM modul, AM part, PLL synthesizer
Page	14	Stereo decoder, RDS / Noise / Multipath
Page	15	μC, Eeprom, Fan, DCC connector
Page	16	Audio control, AF power stage
Page	17	Power supply
Page	18	Connector, Changer interface
Page	19	Exploded view, mechanical partslist
Page	20	Electrical partslist

TECHNICAL DATA

GENERAL	Power supply:	14,4 V
	Quiescent current:	< 2.0 mA
	Playback current:	28 A (4x5 W)

TUNED		07.5 400.1415	
TUNER	FM	87.5 - 108 MHz	grid: 100 kHz search, 100 kHz manual
	MW	531 - 1611 kHz (565 - 186 m)	grid: 9 kHz search, 1 kHz manual
	LW	144 - 288 kHz (2083 - 1042 m)	grid: 9 kHz search, 9 kHz manual

grid: 5 kHz search, 5 kHz manual 5.95 - 6.2 MHz (50.4 - 48.4 m)

Presets: 6 FM1, 6 FM2, 6 FM-AST, 6 SW, 6 MW, 6 LW

Sensitivity 26 dB S/N: FM: 4 μV SW: 28 μV MW: 28 μV

LW: 56 μV

IF (FM / AM):

10.7 MHz

COMPACT CASSETTE

Number of tracks: 2x2 Tape speed: 4,75 cm/s Winding time: 100 s (C60) 40 - 14.000 Hz Frequency response:

0.2% (IEC 386 / DIN 45507) Wow and flutter: S/N ratio (DOLBY OFF): FE: 48 dB (weighted)

CR: 53 dB (weighted)

AMPLIFIER

Output: 4 x 4.5 W sinus (at 10% THD) +/- 12 dB (100 Hz), 2 dB steps Bass: Treble: +/- 12 dB (10 KHz), 2 dB steps

Channel separation: > 30 dBTelefonmute: > -40 dB

CONTROLS

Retrac handle release

set on/off **POWER ⊙**

Short press: Changes the play direction of a DCC or Compact Cassette **EJECT <>**

Long press: Ejects DCC or Compact Cassette

Radio operation: Search tuning upwards NEXT ►

DCC/Compact Cassette operation: Selects next tracks of a DCC/Compact Cassette

CD operation: Next track of actual disc

Radio operation: Manual tuning upwards

DCC/Compact Cassette operation: Fast winding DCC/Compact Cassette

CD operation: Fast forward playback as long as key is depressed

Radio operation: Manual tuning downwards

DCC/Compact Cassette operation: Fast rewind DCC/Compact Cassette CD operation: Fast backward playback as long as key is depressed

⋖ PREV Radio operation: Search tuning downwards

DCC/Compact Cassette operation: Selects previous tracks of a DCC/Compact Cassette

CD operation: Previous track of actual disc

Volume, Bass or Treble down; Balance to left; Fader to rear ¥

Volume, Bass or Treble up; Balance to right; Fader to front

BASS

Bass/Balance selector BAL

TREB

Treble/Fader selector FAD

Audio Mute; interrupts playback of DCC, Compact Cassette or CD (pause) MUTE

Radio operation: Station presets 100 ... 6

CD operation: Disc selection

Dolby Noise Reduction B or C type (only for Compact Cassette) 100

LOUD Short press: Loudness Long press: Audio reset **RST**

Radio operation: Shows the frequency and the selected wave band instead of the station-name DISP

DCC operation: Selects the DCC text mode (only with pre-recorded DCC's) CD operation: Shows total number of tracks and total play time of actual disc

Selector for strong (local) stations LOC

Short press: Traffic information/announcement TA

Long press: Skips a traffic message

BAND

Radio operation: Selects the desired wave band (FM1, FM2, FM3, MW, LW, SW) RND

CD operation: Random track selection of actual disc


Long press: Enters the 'INIT' mode

AST

Radio operation: Auto-Store to program the six strongest stations of the current reception area **SCAN**

CD operation: 10 sec.- playback of each track of actual disc

Selects source (Radio, DCC/Compact Cassette or CD-Changer) SRC



DISPLAY INDICATIONS

AF Tuned station broadcasts RDS information with Alternative Frequencies

DCC A Digital Compact Cassette is in the cassette deck

TAPE-IN A Compact Cassette is in the cassette deck

Radio operation: Preset station (1 out of 6) is selected

DCC/Compact Cassette operation: Indicates side A or B of the DCC/Compact Cassette

LOCAL Searches for strong (local) stations only

Dolby Noise Reduction B or C is switched on (only Compact Cassette)

TP Traffic Program: Indicates that the station broadcasts traffic information

TP-EON A Traffic message is received via Enhanced Other Networks

LOUD Loudness is switched on

TA Traffic Announcement mode is switched on

Radio operation: Wave band and frequency or (FM only) the station name Audio adjustment: Shows the current settings of Bass, Balance, Treble or Fader

DCC operation: Shows track number and elapsed time or text mode(only prerecorded DCC's)

INIT mode: Shows initialization parameters and their settings

AST Auto-Store band chosen (on FM3)

INIT MODE

Select INIT MODE by pressing the BAND key for at least 3 seconds, until a bleep is heard.

The following parameters can be changed when the set is in INIT MODE:

1. Illumination colour

After entering INIT MODE, the display shows 'COLOR'.

Toggle between 'green' or 'orange' colour with the ↑/ ¥keys.

2. Viewing angle

After entering INIT MODE, select the 'VIEW' parameter with the → PREV or NEXT ▶ keys. The display should show 'VIEW 0'.

Select the viewing angle between -1 and 2 with the →/ ¥keys for best legibility of the display.

3. AF mode

After entering INIT MODE, select the 'AF' parameter with the

→ PREV' or NEXT

keys.

The display should show e.g. 'AF ON'.
Select between 'AF ON' or 'AF OFF' with the ♀ or ≚ keys.

If you want to store an RDS station without automatic retuning, you have to do the following:

Tune to the desired station.

After entering INIT MODE, select 'AF OFF'.

Leave the INIT MODE (see below) and store this station.

4. AM wave bands on/off

If you don't want to use the AM wave bands (MW, LW and SW), those bands can be switched off.

After entering INIT MODE, select the 'AM' parameter with the

→ PREV or NEXT

keys.

The display should show e.g. 'AM ON'.
Select between 'AM ON' and 'AM OFF' with the ♀ or ➤ keys.
When you select 'AM OFF', you can choose only between FM1, FM2 and FM3.

To leave the INIT MODE, press briefly the BAND key.

The INIT MODE will be left automatically, when no keys are depressed within 10 seconds.

NOTE:

For informations about how to use the set see the 'Operating Instructions'.

NOTE:

The handling of flat pack IC's is described in Service Information A86-100, dated 1986-07-01.

NOTE:

Switch off power supply before connecting or disconnecting the cassette deck.

NOTE:

Extension cables for front unit and cassette deck are NOT available as serviceparts.

You can build these by using the coded sockets and plugs.

NOTE:

Single buttons of the ornamental plate are NOT available.

If there is an absolute need for single buttons you can take apart a complete delivered plate.

NOTE:

For more information about the RDS feature use the 'computer based training course RDS' which is available at Philips Consumer Service.

Contact:

Philips Consumer Electronics

Philips International Support Centre

Building SBP6

NL 5600 MD Eindhoven

tlx routing indicator: NLMEVAB FAX: + 31 40 73 35 53

CONNECTORBLOCK 22DC811+22DC821

1 2 3 4 5 6 6 7	C B	1 2	4 3 4	5 6 5 6	8 7 8	1
	_	000	_	00	0 0	O 018
12						1

D1: SWITCHED + D2: REMOTE RETURN D3: SIGNAL GND D4: LINE OUT FR	>5 >12 >7 >8	D5: LINE OUT RR D6: LINE OUT FL D7: LINE OUT RL	>9 >10 >11
C1: GND C2: D2B+ (DC821) C3: D2B- (DC821) C4: NC C5: PERM.+	> 28 > 27 > 23 > 17	C6: GND C7: SWITCHED + C8: EXT.IN R (DC821) C9: EXT.IN L (DC821) C10: EXT.IN GND (DC821)	>6 >16 >26 >3 >25
B1: RR+ B2: RR- B3: FR+ B4: FR-	> 22 > 24 > 21 > 22	B5: FL+ B6: FL- B7: RL+ B8: RL-	> 13 > 19 > 19 > 14
A1: TEL.MUTE A2: GND A3: NC A4: PERM.+	> 15 > 18 > 4	A5: SWITCHED + A6: EXT.ILL. A7: IGN.KEY+ (FUSE) A8: GND	>5 >2 >1 >18

Key- and Display-test, Romcode version front μ C

- Separate the front unit assy from the set.
- Connector 1801: connect pin 1 + 10 to ground and pin 4 to 5 V Display shows 'KEY TEST'.

Key-test

When pushing the buttons the concerned indication must be displayed.


Display-test

- Hold preset 1 figure Preset 1 must be displayed
- Hold preset 2 all display-segments are blanked
- Hold preset 3 figure Preset 2 must be displayed


Romcode version

- Hold preset 4 - the software version of the front μC must be displayed (e.g. RC 04)

Preset 1



Preset 3



Checks 22DC811 + 22DC821

Check	Band					0 0
Varicap-	AM			144 KHz	IC 7251 PIN 15	> 2,2 V
voltage				6200 KHz		< 6,0 V
0	FM			87,5 MHz	FM 1008 PIN 15	> 1,0 V
				108 MHz		< 6,0 V
Demodulated AM - level	AM	990 KHz, 10 mV 1 KHz, 30% AM	Ŷ		IC 7201 PIN 12	350 +/- 100 mV
Demodulated FM - level	FM	93,0 MHz, 1 mV ∆ f = 22,5 KHz f mod = 1 KHz	Ŷ		FM 1008 PIN 2	160 mV
		93,0 MHz, 1 mV Δf = 6,75 KHz f mod = 19 KHz				45 mV
		93,0 MHz, 1 mV Δ f = 3,75 KHz f mod = 57 KHz				20 mV
S/N ratio	FM	93,0 MHz, 1 mV Δf = 22,5 KHz	Ŷ		Connectorblock Section B	1,4 V => Referencelevel (dB)
		f mod = 1 KHz			PIN 3 + PIN 5	
		93,0 MHz, 1 mV				Referencelevel > - 50 dB
		$\Delta f = 22,5 \text{ KHz}$,		
		unmodulated				
	AM	990 KHz, 2mV				1,4 V
		30 % mod., 1KHz			·	=> Referencelevel (dB)
		990 KHz, 2mV				Referencelevel > - 48 dB
		unmodulated				
Wide band AGC switch	A M	990 KHz, 2mV without modulation	Ŷ		IC 7201 PIN 1	V1 ~ 6,5 V
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		990 KHz, 200mV without modulation				V2 ~ 7,0 V (V2 - V1 > 0,5 V)
FM - search - sensitivity	FM	94,1 MHz, 160 μV Δ f = 22,5 KHz	Ŷ	LO - Se	arch tuning	tuning stop after 2. run
		f mod = 1 KHz				
		94,1 MHz, 250 μV Δf = 22,5 KHz		LO - Se	arch tuning	tuning stop after 1. run
		f mod = 1 KHz		DV C-	arch tuning	no tuning stop
		94,1 MHz, 4 μV Δ f = 22,5 KHz		DX - 56	earch tuning	no tuning stop
		f mod = 1 KHz	-	DV C	earch tuning	tuning stop after 1. run
		94,1 MHz, 10 μ V $\Delta f = 22,5 \text{ KHz}$		DX - 56	earch tuning	turning stop alter 1. van
		f mod = 1 KHz		10 0	earch tuning	tuning stop after 2. run
AM - search- sensitivity	A M	990 KHz, 240 μV 1 KHz, 30% AM	\\ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\			
		990 KHz, 370 μV 1 KHz, 30% AM		LO - Se	earch tuning	tuning stop after 1. run
		990 KHz, 22 μV 1 KHz, 30% AM		DX - Se	earch tuning	no tuning stop
		990 KHz, 50 μV 1 KHz, 30% AM		DX - Se	earch tuning	tuning stop after 1. run

CHECK LOW VOLTAGE CONTROL CIRCUIT

1: Supply voltage 14.4 V

Set switched on

Pos. 7701, pin 7 = 4.7 V + -400 mV

2: Supply voltage 8.3 V +/- 900 mV

Set switches off automatically

Pos. 7701, pin 7 = 0.5 V + /-500 mV

3: Supply voltage 14.4 V

Set switches on

Pos. 7701, pin 7 = 4.7 V + /-400 mV

Adjustments 22DC811 + 22DC821

Adjustment	Band	Ø	••		•	0 0
α - 3 dB	FM	94,1 MHz, 1 mV ∆ f = 22,5 KHz f mod = 1 KHz	Ŷ		Connectorblock Section B PIN 3 + PIN 5	1,4 V => Referencelevel (dB)
		94,1 MHz, 7 μV Δ f = 22,5 KHz f mod = 1 KHz		R 3105		Referencelevel - 3 dB
10 dB Channel- separation	FM	94,1 MHz, 120 μ V Δ f = 22,5 KHz f mod = 1 KHz (right channel only) Stereo-Pilot 10%	Ŷ	R 3630	Connectorblock Section B PIN 3 <-> PIN 5	10 dB (+/- 1 dB)
Channel - separation maximum	FM	94,1 MHz, 10 mV Δ f = 22,5 KHz f mod = 1 KHz (right channel only) Stereo-Pilot 10%	(*)	R 3608	Connectorblock Section B PIN 3 <-> PIN 5	max. (ca. 34 dB)
		Check	α-3dBaga	ain and adjust if r	necessary	
Noise - detector	FM	98,0 MHz, 1 mV Δ f = 75 KHz f mod = 40 KHz	Ŷ	R 3426	IC 7420 PIN 14	850 +/- 50 mV (AC)


Do not adjust coils 5210 and 5228 (AM-PART), because they are correctly preadjusted by supplier!

! NOTE


FM- and AM- search sensitivities are only adjustable with a special equipment via software. If you get sets with search sensitivities out of specification, send them to factory-service in Wetzlar until further notice.

Philips Apparatefabrik Wetzlar Department SP-CS Philipsstrasse 1 D - 35576 Wetzlar GERMANY


SWITCH PWB





LCD PWB




FRONT CIRCUIT (SWITCH + LCD)








STEREO DECODER RDS / NOISE / MULTIPATH



uC / EEPROM / FAN / DCC CONNECTOR



28: 5,0 V

29: GND

13: GND

14: 5,0 V

43: 2.5 V


44: 5,0 V (RADIO OP.)

65: 5,0 V


66: 5,0 V

80: 5,0 V (OSC)

AUDIO CONTROL / AF POWER STAGE




POWER SUPPLY



Pos.7701 1: 13,6 V 2: 2,2 V 3: 7,0 V 4: 2,3 V 5: GND 6 - 8: 5,0			
Pos.7702 1: 14,2 V 2: 2,5 V 3: 0,0 V 4: 8,4 V 5 - 8: GNI			
Pos.7703 1: 14,2 V 2: GND 3: 5,0 V	MC7805		
Pos.7705 1: 14,2 V 2: 2,5 V 3: 0,0 V 4: 8,4 V 5 - 8: GNI			
Pos.7706 B: 13,5 V C: 14,2 V E: 14,4 V	BD438		
Pos.7708 B: 0,0 V C: 10 V E: GND	BC847		
Pos.7709 B: 0,0 V C: 5,0 V E: GND	BC847		
Pos.7710 B: 14 V C: 10,2 V E: 14,4 V	BC857		
Pos.7711 B: 13,8 V C: 14,4 V E: 14,5 V	BC857		
Pos.7712 B: 0,9 V C: 0,3 V (E: GND		4 V (OFF)	
Pos.7713 B: 0,8 V C: 0,2 V E: GND	BC847		
Pos.7714 B: 0,1 V (0 C: 0,8 V (0 E: GND	0,0 / (NC	V (OFF)	
Pos.7716 B: 0,1 V C: 5,0 V E: 0,0 V	BC847B		
Pos.7731 1: 5,0 V } 2: 5,0 V } 3: 0,1 V } 4: 0,1 V } 5: 5,0 V }		E L OPERATI	ON
-20.00 (Mar SA) (CCP)			


CONNECTOR / CHANGER INTERFACE



Pos. 7752 BC847 B: 0,7 V (OFF) / 0,8 V (ON) C: 0,0 V (OFF) / 0,1 V (ON) E: GND Pos. 7755 BC817-40 B: 0,0 V / 0,5 V (LINE MUTE) C: 0,1 V E: GND Pos. 7756 BC817-40 B: 0,0 V / 0,5 V (LINE MUTE) C: 0,1 V E: GND Pos. 7757 BC817-40 B: 0,0 V / 0,5 V (LINE MUTE) C: 0.1 V E: GND Pos. 7758 BC817-40 B: 0,0 V / 0,5 V (LINE MUTE) C: 0,1 V E: GND Pos. 7781 L272 MP 1: 1,0 V (RED DISPLAY) / 13,3 V (GREEN DISPLAY) 3: 13,3 V (RED) / 1,0 V (GREEN) 4: GND 5: 3,4 V 6: 5,1 V (RED) / 0,1 V (GREEN) 7: 3,4 V 8: 13,3 V (RED) / 1,0 V (GREEN)

Pos. 7783 BC857

B: 12 V (OFF) / 13,9 V (ON) C: 12,3 V (OFF) / 0,0 V (ON) E: 12,8 V (OFF) / 13,9 V (ON)



MISCELLANEOUS 1201 4822 242 72076 CRYSTAL 10,7 MHZ 1202 4822 242 77876 CRYSTAL 10,7 MHZ 1203 4822 242 77883 CERAM FILTER SFE10,7MS318-D 1204 4822 242 71873 CERAM FILTER SFE10,7MS318-D 1251 4822 242 71874 CRYSTAL 4,000 MHZ 4,00	2406 4822 122 33216 CAP.CHIP 100NF 10 2409 4822 124 22846 ELCAP 2.2UF 20 2410 5322 122 31946 CAP.CHIP 27PF 10 2411 5322 122 31946 CAP.CHIP 27PF 10 2411 5322 122 31946 CAP.CHIP 27PF 10 2412 4822 122 33496 CAP.CHIP 100NF 10 2420 2412 4822 123 33496 CAP.CHIP 100NF 10 2420 2424 5322 122 33538 CAP.CHIP 10PF 27PF 10 2420 4822 122 33538 CAP.CHIP 10PF 20 2427 4822 122 38614 CAP.CHIP 10NF 20 2427 4822 122 38165 CAP.CHIP 10NF 20 2430 4822 122 33177 CAP.CHIP 10NF 20 2430 4822 124 3401 ELCAP 4.7UF 2432 4822 122 33496 CAP.CHIP 10NF 20 2433 5322 122 32654 CAP.CHIP 10NF 20 2433 5322 122 32654 CAP.CHIP 10NF 20 2435 4822 122 33178 CAP.CHIP 10NF 20 2435 4822 122 33496 CAP.CHIP 10NF 20 2435 4822 122 33496 CAP.CHIP 10NF 20 2435 4822 122 33178 CAP.CHIP 10NF 20 2436 4822 122 33178 CAP.CHIP 10NF 20 2436 4822 122 33178 CAP.CHIP 10NF 20 2606 4822 122 33296 CAP.CHIP 10NF 20 2606 4822 122 33296 CAP.CHIP 10NF 10 2608 4822 122 33496 CAP.CHIP 10NF 10 2610 4822 124 33281 ELCAP 10F 2611 4822 124 33281 ELCAP 20 2612 4822 122 33496 CAP.CHIP 10NF 10 2613 4822 122 33496 CAP.CHIP 10NF 10 2613 4822 122 33496 CAP.CHIP 10NF 10 2613 4822 122 33496 CAP.CHIP 10NF 10 2615 4822 122 33496 CAP.CHIP 10NF 10 2616 5322 123 3338 CAP.CHIP 10NF 10 2616 5322 123 3338 CAP.CHIP 10NF 10 2616 5322 123 3338 CAP.CHIP 10NF 20 2617 5322 122 33531 CAP.CHIP 10NF 20 2617 5322 122 33531 CAP.CHIP 10NF 20 2617 5322 122 33531 CAP.CHIP 10NF 20 2618 5322 122 33531 CAP.CHIP 10NF 20 2618 5322 122 33531 CAP.CHIP 10NF 20 2617 5322 122 33531 CAP.CHIP 10NF 20 2618 5322 123 3358 CAP.CHIP 10NF 20 2617 5322 122 33531 CAP.CHIP 10NF 20 2618 5322 122 33531 CAP.CHIP 10NF 20 2618 5322 122 33531 CAP.CHIP 10NF 20 2617 5322 122 33531 CAP.CHIP 10NF 10 2704 4822 124 3358 ELCAP 10F 20 20 20 20 20 20 20 20 20 20 20 20 20	50V 2924 4822 122 33178 CAP.CHIP 50V 2927 4822 122 33496 CAP.CHIP 50V 3101 4822 051 20478 RES.CHIP 50V 3101 4822 051 20478 RES.CHIP 190 63V 3103 4822 051 20221 RES.CHIP 50V 3105 4822 100 11163 POTM.TRIM X7R50V 3109 4822 051 20478 RES.CHIP X7R63V 3201 4822 051 20471 RES.CHIP X7R50V 3202 4822 051 20102 RES.CHIP X7R50V 3203 4822 051 20102 RES.CHIP X7R63V 3201 4822 051 20102 RES.CHIP X7R63V 3204 4822 051 20223 RES.CHIP X7R63V 3204 4822 051 20102 RES.CHIP X7R63V 3204 4822 051 20147 RES.CHIP X7R63V 3204 4822 051 20147 RES.CHIP X7R63V 3204 4822 051 20147 RES.CHIP X7R63V 3204 4822	4R70 5% 0,1W 27K00 5% 0,1W 560R00 5% 0,1W 470R00 5% 0,1W 1K00 5% 0,1W 1K00 5% 0,1W 22K00 5% 0,1W 33K00 5% 0,1W 1K50 5% 0,1W 1K50 5% 0,1W 1K50 5% 0,1W 4K70 5% 0,1W 4K70 5% 0,1W 1K00 5% 0,1W 4K70 5% 0,1W 1K00 5% 0,1W 4K70 5% 0,1W 1K00 5% 0,1W 1K50 5% 0,1W	3671 4822 051 20322 RES.CHIP 12 3676 4822 051 20152 RES.CHIP 12 3677 4822 051 20323 RES.CHIP 12 3677 4822 051 20323 RES.CHIP 18 3678 4822 051 20123 RES.CHIP 12 3679 4822 051 20132 RES.CHIP 18 3680 4822 051 20323 RES.CHIP 18 3680 4822 051 20324 RES.CHIP 10 3705 4822 051 20104 RES.CHIP 10 3706 4822 051 10273 RES.CHIP 10 3707 4822 051 10273 RES.CHIP 10 3707 4822 051 10273 RES.CHIP 10 3707 4822 051 10154 RES.CHIP 10 3707 4822 051 10154 RES.CHIP 10 3714 4822 051 10154 RES.CHIP 15 3714 822 051 20224 RES.CHIP 15 3713 4822 051 20224 RES.CHIP 12 3723 4822 051 20224 RES.CHIP 12 3723 4822 051 20224 RES.CHIP 12 3723 4822 051 20224 RES.CHIP 12 3730 4822 051 20224 RES.CHIP 12 3731 4822 051 20224 RES.CHIP 12 3732 4822 051 20224 RES.CHIP 12 3734 4822 051 20224 RES.CHIP 12 3736 4822 051 20473 RES.CHIP 12 37374 RES.CHIP 12 3738 RES.CHIP 12 3741 RES.CHIP 12 3752 RES.CHIP 12 3753 RES.CHIP 12 3754 RES.CHIP 12 3754 RES.CHIP 16 3755 RES.CHIP 16 3750 RES.CHIP 16 3751 RES.CHIP 16 3752 RES.CHIP 16 3753 RES.CHIP 16 3754 RES.CHIP 16 3755 RES.CHIP 16 3759 RES.CHIP 16 3759 RES.CHIP 16 3760 RES.CHIP 16 3760 RES.CHIP 16 3771 RES.CHIP 16 3772 RES.CHIP 16 3773 RES.CHIP 16 3774 RES.CHIP 16 3774 RES.CHIP 16 3775 RES.CHIP 16 3779 RES.CHIP 16 3789 RES.CHIP 16 3799 RES.CHIP	K00 50 50 50 30 0K00 50 0K00 5% 0,1W K00 2% 0,25W 0E 5% 0,5W 0K00 2% 0,25W 0K00 5% 0,1W 0C0 0C0 0C0 0C0 0C0 0C0 0C0 0C0 0C0 0C	5252 4822 152 20678 COIL 5402 4822 157 50975 COIL 5701 4822 157 50975 COIL 5701 4822 157 53669 COIL ASSY 5702 5916 4822 152 20677 COIL DIODES 6221 4822 130 82982 DIODE 6230 5322 130 34337 DIODE, CHIP 6301 4822 130 30621 DIODE 6420 5322 130 34337 DIODE, CHIP 6430 5322 130 34337 DIODE, CHIP 6470 4822 130 30621 DIODE 6661 4822 130 30621 DIODE 6703 4822 130 81196 RECTIFIER 6704 4822 130 81196 RECTIFIER 6705 4822 130 81196 RECTIFIER 6750 4822 130 8196 RECTIFIER 6750 4822 130 30621 DIODE 6765 4822 130 30621 DIODE 6765 4822 130 30621 DIODE 6765 4822 130 3094 DIODE, REF. 6751 4822 130 3094 DIODE, REF. 6751 4822 130 32904 DIODE 6765 4822 130 32904 DIODE 6761 4822 130 82981 LED 6802 6816 4822 130 82981 LED 6804 4822 130 82981 LED 6804 4822 130 82981 LED 6804 4822 130 82981 LED 6904 4822 130 30621 DIODE 6905 5322 130 34337 DIODE, CHIP TRANSISTORS AND IC's 7230 4822 209 72247 IC 7230 4822 209 32995 IC 7302 5322 209 14542 IC 7303 4822 130 42705 TRANS. CHIP 7351 4822 209 32995 IC 7401 4822 209 32995 IC 7401 4822 209 31644 IC 7420 4822 209 31644 IC 7420 4822 209 31644 IC 7421 4822 130 42353 TRANS. 7666 4822 130 42353 TRANS. 7675 4822 130 42353 TRANS. 7676 4822 130 42353 TRANS. 7677 4822 209 72227 IC 7703 4822 209 72227 IC 7704 4822 209 30859 IC 7705 4822 209 72227 IC 7706 4822 130 61233 TRANS. CHIP 7710 4822 130 61233 TRANS. CHIP 7711 4822 130 61233 TRANS. CHIP 7712 4822 130 61233 TRANS. CHIP 7713 4822 130 61233 TRANS. CHIP 7714 4822 130 61233 TRANS. CHIP 7717 4822 130 61233 TRANS. CHIP 7718 4822 130 61233 TRANS. CHIP 7719 4822 130 61231 TRANS.	33UH 33UH 33UH 1MH POWER SUPPLY 10MUH BB512 BAV99 1N4148 1N4148 1N4148 BAV99 BAV99 1N4148 1.5KE27P S5566B 1N4148 1.5KE27P S5566B 2V55-C5V6 1N4148 BZV85-C5V6 BZV85-C5V6 BZV85-C5V6 TN4148 BAV99 TEA6200/V2 2SK507F TSA6057/C1 BC847 TDA7313/ HEF4066BT BC847 TDA7313/ HEF4066BT BC847 TDA7374V LA2000 TDA7330 TL074IN BC847 TDA7374V LA2000 TDA7330 TL074IN BC847 TDA7374V LA2000 TDA7330 TL074IN BC847 TDA75191/V3 BC847 BC857 BC847
2251 4822 122 32566 CAP.CHIP 3,9NF 10% X7R 63V 2252 4822 122 33177 CAP.CHIP 10NF 20% X7R 50V 2253 5322 122 32654 CAP.CHIP 22NF 10% X7R 63V 2254 4822 122 33608 CAP.CHIP 39NF 10% X7R 63V 2255 4822 121 43711 CAP.CHIP 22NF 10% X7R 63V 2256 5322 122 32654 CAP.CHIP 22NF 10% X7R 63V 2257 4822 124 3281 ELCAP 33UF 20% 16V 2258 4822 124 80453 ELCAP 10NF 20% X7R 50V 2259 4822 124 80453 ELCAP 10UF 20% 10V 2263 4822 051 20008 RES.CHIP JMPR 2301 2306 4822 124 23282 ELCAP 1UF 20% 50V 2307 4822 124 23279 ELCAP 2UF 20% 16V 2308 4822 124 23582 ELCAP 2UF 20% 16V 2309 4822 124 23486 ELCAP 2UF 20% 16V 2309 4822 124 23582 ELCAP 2UF 20% 16V <	2707 4822 124 41017 ELCAP 10UF 2708 4822 124 41017 ELCAP 10UF 2709 4822 122 33496 CAP.CHIP 100NF 109 2710 4822 122 33496 CAP.CHIP 100NF 109 2711 4822 124 23282 ELCAP 1UF 209 2712 4822 124 80815 ELCAP 470UF 209 2713 4822 124 41017 ELCAP 10UF 2714 4822 122 33496 CAP.CHIP 100NF 109 2715 4822 124 40017 ELCAP 10UF 2716 4822 124 3082 ELCAP 1UF 209 2717 2719 4822 122 33566 CAP.CHIP 100NF 209 2717 2719 4822 122 33566 CAP.CHIP 3,9NF 109 2720 4822 122 33177 CAP.CHIP 10NF 209 2730 4822 122 33177 CAP.CHIP 10NF 209 2731 4822 122 33496 CAP.CHIP 10NF 209 2732 4822 122 33177 CAP.CHIP 10NF 209 2731 4822 122 33496 CAP.CHIP 3,9NF 109 2732 4822 124 23504 ELCAP 2.2UF 209 2751 4822 124 23504 ELCAP 33UF 209 2751 4822 124 23566 CAP.CHIP 3,9NF 109 2751 4822 124 23566 CAP.CHIP 3,9NF 109 2752 4822 124 23281 ELCAP 2200UF 209 2752 4822 122 32566 CAP.CHIP 3,9NF 109 2755 4822 124 23281 ELCAP 2200UF 209 2752 4822 124 23281 ELCAP 2200UF 209 2752 4822 124 23281 ELCAP 33UF 209 2764 4822 122 33177 CAP.CHIP 3,9NF 109 2765 4822 124 23285 ELCAP 1UF 2765 4822 124 23285 ELCAP 30UF 209 2764 4822 122 33177 CAP.CHIP 3,9NF 109 2765 4822 124 23285 ELCAP 30UF 209 2768 4822 124 23285 ELCAP 1UF 2768 4822 124 23285 ELCAP 1UF 2769 4822 124 23285 ELCAP 1UF	16V 3605 4822 051 20224 RES.CHIP 16V 3606 4822 051 20104 RES.CHIP X7R63V 3607 4822 051 20823 RES.CHIP 50V 3608 4822 100 12071 POTM. 50V 3609 4822 051 20471 RES.CHIP 16V 3610 4822 051 20273 RES.CHIP 16V 3611 4822 051 20152 RES.CHIP 50V 3613 4822 051 20152 RES.CHIP 50V 3614 4822 051 20102 RES.CHIP 16V 3614 4822 051 20102 RES.CHIP 3615 4822 051 20109 RES.CHIP 3616 4822 051 201047 RES.CHIP 3616 4822 051 20273 RES.CHIP 3624 4822 051 20273 RES.CHIP 3624 4822 051 20273 RES.CHIP 3626 4822 051 20273 RES.CHIP 3626 4822 051 20273 RES.CHIP 3626 4822 051 20104 RES.CHIP 3626 4822 051 20222 RES.CHIP 3627 4822 051 20222 RES.CHIP 3638 4822 051 20225 RES.CHIP 3638 4822 051 20273 RES.CHIP 3638 4822 051 20225 RES.CHIP 3638 4822 051 20273 RES.CHIP 3638 4822 051 20273 RES.CHIP 3638 4822 051 20273 RES.CHIP 3638 4822 051 20225 RES.CHIP 3638 4822 051 20225 RES.CHIP 3638 4822 051 20225 RES.CHIP 3638 4822 051 20273 RES.CHIP 3638 4822 051 20225 RES.CHIP 3638 4822 051 20255 RES.CHIP 3638 4822 051 20255 RES.CHIP 3638 4822 051 20255 RES.CHIP 3638 4822 051 20273 RES.CHIP 3638 4822 051 20256 RES.CHIP 3638 4822 051 20256 RES.CHIP 3638 4822 051 20256 RES.CHIP 3638 RES.CHIP 3642 4822 051 20473 RES.CHIP 3642 4822 051 20473 RES.CHIP 3642 4822 051 20473	220K00 5% 0,1W 100K00 5% 0,1W 82K00 5% 0,1W EVNDXAA03B25 470R00 5% 0,1W 27K00 5% 0,1W 1K50 5% 0,1W 12K00 0R00 JUMP. (0805) 1K00 5% 0,1W 27K00 5% 0,1W 27K00 5% 0,1W 150K00 5% 0,1W 150K00 5% 0,1W 27K00 5% 0,1W 470K00 5% 0,1W 27K00 5% 0,1W 470K00 5% 0,1W 27K00 5% 0,1W 27K00 5% 0,1W 470K00 5% 0,1W 27K00 5% 0,1W 27K00 5% 0,1W 27K00 5% 0,1W 27K00 5% 0,1W 470K00 5% 0,1W 27K00 5% 0,1W	3795 4822 050 12709 RES.METAL FILM 276 3809 3819 4822 051 20123 RES.CHIP 126 3825 4822 051 20154 RES.CHIP 156 3828 4822 051 20154 RES.CHIP 156 3902 3904 4822 051 20153 RES.CHIP 156 3910 4822 051 20102 RES.CHIP 156 3913 4822 051 20103 RES.CHIP 156 3915 4822 051 20153 RES.CHIP 156 3916 4822 051 20153 RES.CHIP 157 3919 4822 051 20153 RES.CHIP 157 3919 4822 051 20153 RES.CHIP 157 3922 3924 4822 051 20153 RES.CHIP 157 3925 4822 051 20153 RES.CHIP 157 3926 4822 051 20153 RES.CHIP 157 3927 4822 051 20104 RES.CHIP 100 3951 4822 051 20108 RES.CHIP 107 3951 4822 051 20108 RES.CHIP 157 5205 4822 152 20678 COIL 331 5205 4822 152 20677 COIL 107 5206 4822 157 52983 COIL 221	1% 0,4W (00 5% 0,1W (00 5% 0,	7662 4822 130 42353 TRANS. 7675 4822 130 61233 TRANS. 7676 4822 130 61233 TRANS. 7701 4822 209 31373 IC 7702 4822 209 72227 IC 7703 4822 209 80891 IC 7704 4822 130 61233 TRANS.CHIP 7705 4822 130 40995 TRANS.CHIP 7708 4822 130 42705 TRANS.CHIP 7709 4822 130 61233 TRANS.CHIP 7710 4822 130 61233 TRANS.CHIP 7711 4822 130 61233 TRANS.CHIP 7712 4822 130 61233 TRANS.CHIP 7713 4822 130 42705 TRANS.CHIP 7714 4822 130 61233 TRANS.CHIP 7715 4822 130 61233 TRANS.CHIP 7716 7717 4822 130 61233 TRANS.CHIP 7717 4822 130 61233 TRANS.CHIP 7718 4822 130 42705 TRANS.CHIP 7719 4822 130 42705 TRANS.CHIP 7711 4822 130 42705 TRANS.CHIP 7713 4822 130 42705 TRANS.CHIP	BFS19 BC857 BC857 L4949 L4916 MC7805CT BC857 L4916 BD438 BC847 BC847 BC857 BC857 BC857 BC847 BC817-40 MSM6307GS-VK TCA0372DP1 BC857 BC817-40
2356 4822 124 23504 ELCAP 2.2UF 20% 50V 2357 4822 124 80726 ELCAP 2.2UF 20% 50V 2361 4822 124 23504 ELCAP 2.2UF 20% X7R 50V 2401 4822 124 23504 ELCAP 2.2UF 20% 50V 2402 4822 124 23504 ELCAP 2.2UF 20% 50V 2403 4822 124 41017 ELCAP 10UF 16V 2404 4822 122 33177 CAP.CHIP 10NF 20% X7R 50V	2903 4822 122 33342 CAP.CHIP 33NF 109 2904 4822 122 33342 CAP.CHIP 33NF 109 2905 4822 124 41017 ELCAP 10UF 2911 5322 122 32268 CAP.CHIP 470PF 109	X7R63V 3663 4822 051 20121 RES.CHIP X7R63V 3664 4822 051 20332 RES.CHIP 16V 3665 4822 051 20332 RES.CHIP	68K00 120R00 3K30 3K30 68K00 68K00 22K00 120R00	5210 4822 152 20683 COIL AD 5228 4822 156 31021 COIL AD 5230 4822 157 53575 COIL 3,3 5231 4822 157 50975 COIL 1M	JH 10% J.28MUH J.1,22UH UH H MUH		72 075

PCS 72 075



22DC811/00R 22DC821/00R 5101

ce Information

The exchange procedure for complete sets is no longer valid. Repairs of faults belonging to the set can now be done in your service shop. The hints on the backside can maybe help vou in some cases.

Because of some intermittend effects with sets built with RC 1 we recommend to update these radios to RC 2. Use IC 4822 209 33973 on pos. 7911.

For other changes and modifications of the sets see also Service Newsletters from issue 1994-W 02 onwards.

2. For the DCC tapedecks use the CENTRAL REPAIR PROCEDURE of Philips Consumer Service from now on.

Information about this procedure (same as for CD deck CMX200) you can get from

Mr. Cor Lieberwirth Philips Consumer Electronics B.V. Philips Consumer Service Beukenlaan 2, Building SBP 5 5600 MD Eindhoven The Netherlands

All sets 22DC811 and 22DC821 have a DCC deck with software RC26 (4822 691 21024). This decks will gradually be replaced by RC27 - versions (4822 691 10442) in service stock of Consumer Service Eindhoven.

A sticker on the backside of the digital print shows the version:

DCC DA26

RC26 (OTP)

DCC DA26-077

RC26 (MASK)

DCC DA27

RC27 (OTP)

DCC DA27-077

RC27 (MASK)

RC27 deck software is only usable with radio software RC2!

22DC811 and 22DC821 sets with RC1 must get a software update to RC2 when a RC27 deck will be installed!

Use also the insulation cover 4822 423 41288 to protect the flex foil against damage and the control PWB against short circuit with the frame! (see Service Manual 22DC822)

When 22DC811 is updated to RC2 it will show some different behaviour:

- 1. After Power on DCC821 appears instead of DCC811
- 2. During volume adjustment VOL XX appears in
- 3. BLEEP is disabled (solder a wire between pins 16 and 26 of Main processor to enable BLEEP again)

4822 725 23525





COMPLAINT, SET RELATED	REASON	SOLUTION IN PRODUCTION	SERVICE SOLUTION
No function/obscure behaviour	Set with OTP-IC, software crash	Only mask programmed IC's used	Change OTP into mask (see Service Newsletter 1994-W 02)
	EEPROM defect	Check incoming goods	Send set to Wetzlar for new programming
Switch off by itself, RDS mutes	Wrong value of chip capacitor pos.2911	Value changed into 33 nF	Change pos.2911 into 33 nF (see Service Newsletter 1994-W 02)
No sound	TDA7374 defect, wrong speaker connection	Sticker added on retrac	Exchange TDA 7374, inform customer
No function, no display	Bad soldered frontconnector	Better check	Solder all pins
COMPLAINT, DECK RELATED			
Deck no function, no insert possible	Fixing hook of pivot plate broken Hang out of loading, burr at locking lever Servornotor loose, bracket broken Loading sticks at guiding rod Cassette retainer of carrier/lift assy out of shape Control PWB defect	Hook changed in production Locking lever modified in production Modification of bracket Guiding rod changed in production Modification of retainer Check incoming goods	Exchange deck Exchange deck Exchange deck Exchange deck Exchange carrier/lift assy Exchange control PWB
Drift + Flutter	Pivot plate not greased	Capstan bearing greased separately	Grease bearing
DCC interruptions, TAPE displayed while DCC	Flex foil at control PWB broken	Mounting of PWB changed in production	Exchange control PWB
DCC and/or analog cassette no playback	Head dirty		Clean head, ask customer for regular cleaning Exchange head, new alignments necessary (see Manual)
No sound from tape deck	Audio PWB defect	Check incoming goods	Exchange PWB, new alignments necessary (see Manual)
No DCC playback when warm	Bad adjustment of capstan	Better check	Exchange deck
No or bad sound from DCC	Digital/DAC PWB defect	Check incoming goods	Exchange PWB, new alignments necessary (see Manual)
Cassette jammed	Carrier/lift and lift rod jammed	Improvement of carrier/lift assy	Exchange carrier/lift assy